

LA-UR-17-28394

Approved for public release; distribution is unlimited.

Title: Tunable room-temperature single-photon emission at telecom wavelengths from sp³ defects in carbon nanotubes

Author(s): He, Xiaowei; Hartmann, Nicolai F; Ma, Xuedan; Kim, Younghee; Ihly, Rachelle; Blackburn, Jeffery L; Gao, Weilu; Kono, Junchiro; Tanaka, Takeshi; Yomogida, Yohei; Hirano, Atsushi; Kataura, Hiromichi; Htoon, Han; Doorn, Stephen K

Intended for: 2017 CINT user meeting, 2017-09-25/2017-09-27 (Santa Fe, New Mexico, United States)

Issued: 2017-09-15

Disclaimer:


Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the Los Alamos National Security, LLC for the National Nuclear Security Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.



Tunable room-temperature single-photon emission at telecom wavelengths from sp^3 defects in carbon nanotubes

Xiaowei He¹, N. F. Hartmann¹, Xuedan Ma¹, Younghee Kim¹, Rachelle Ihly², Jeffrey L Blackburn², Weilu Gao³, Junichiro Kono³, Yohei Yomogida⁴, Atsushi Hirano⁴, Takeshi Tanaka⁴, Hiromichi Kataura⁴, Han Htoon¹, Stephen K Doorn¹

¹CINT, MPA, Los Alamos National Laboratory, USA; ²CMSC, National Renewable Energy Laboratory, USA; ³ECE, Rice University, USA; ⁴NRI, AIST, Japan




LA-UR-

Introduction

Single-photon sources (SPSs) are the enabling materials required for quantum photonics, quantum information processing and quantum computing. Developing room-temperature SPS at telecom band (1.3-1.55 μm) remains a significant material challenge.

Harnessing exciton localization at defect site in low-dimensional nanomaterials such as single wall carbon nanotube (SWCNT) is a promising route to achieve room-T single-photo emission (SPE).




In this work, we demonstrate that solitary sp^3 defects on SWCNTs paired with nanotube structural diversity can generate room-T SPE spanning the entire telecom band.

[1] X. Ma et al. *Nat. Nanotechnol.*, **2015**, *10*, 671. [2] Nicholai F. Hartmann et al. *Nanoscale.*, **2015**, *7*, 20521. [3] Y. Piao et al., *Nature Chem.*, **2013**, *10*, 840.



Experimental Setup

- Home-made confocal microscope system
- Superconducting nanowire single photon detector
- Single CNT optical imaging and spectroscopy
- Quantum optical measurements of individual CNTs




Tune Defect-emission Wavelength

- Generation of sp^3 defects on CNTs by solution based chemical doping — aryl diazonium functionalization
- Introduction of new red shifted emitting states E_{11}^* and E_{11}^{*-}
- Tuning the defect-emission wavelength to telecom band by selecting CNTs with different diameters




Room-T SPE at Telecom Band



- Ultra high single photon purity with $g^2(0) \sim 0.01$.
- Exceptional emission stability approaching short noise limitation.
- Room-T operation at Telecom O and C band.

Xiaowei He et al., *Nat. Photon*, **2017**, *11*, 577.

Trends in Quantum Emission Behaviors



- Above 60% of the doped CNTs show the $g^2(0)$ lower than 0.1.
- High emission stability and high single photon purity exist for all three chiralities with emission range from 1.1 to 1.6 μm .
- The life time of defect emission shows dependence on tube diameters, the larger the diameter, the shorter the life time.



Xiaowei He et al., *Nat. Photon*, **2017**, *11*, 577.

Summary and Outlook

- Room-T operation at critical telecom wavelength (1.3 and 1.55 μm).
- High single photon purity ($\sim 99\%$)
- Short noise limited emission ability ($\sigma_{QE}/\sigma_{SN} \sim 1$)
- High emission rates (10^{-5} - 10^{-7} s^{-1})

What is next?

- Developing electrical-driven SPEs from doped CNTs [4]
- Investigating photon Indistinguishability of the defect emission by coupling to plasmonic civilities [5]
- Realizing wavelength-controllable defect emission through diverse structures of CNTs



[4] Svetlana Khasminkaya et al., *Nat. Photon*, **2016**, *10*, 420.

[5] Yue Luo et al., *Nature commun*, under review.

